



# INTERCHANGEABLE COMBINE HEADS

## Floating Row Crop Head

- Fixed row spacing set at 30" row spacing
- Floating row units with rotary shoes for uniform cutting height
- Patented gathering belt designed for smooth, uninterrupted material flow
- John Deere cutting knives and drive components
- Mini cleat pattern feeding belt for quicker cleanout between plots
- Easy open, hinged, access panels for maintenance
- Hydraulically driven, speed adjustable from operator's seat
- Adjustable, hinged, mounted row dividers



## Corn Head

- ALMACO/John Deere two-row corn head
- Drag chain feeder housing provides aggressive and even feeding for increased capacity
- Hydraulically drive, with speed adjustable from operator's seat
- Adjustable row spacings from 30" to 40"
- Adjustable stripper plates





## Standard Row Crop Head

- Fixed row spacings available in 30” to 40” range
- Hydraulically drive, speed adjustable from operators seat
- Adjustable gauge wheels to adjust cutter knife height
- John Deere gathering belt and cutting knife
- Mini cleat pattern feeding belt
- Quick release side access panels for maintenance
- Belt feed heads provide rapid and thorough clean-out
- Adjustable-height gauge wheels on header provide superior flotation in poor field conditions and consistent cutting height
- Also available with adjustable row spacing



## Standard Platform Head

- Available with 39”, 45”, 51”, 57” or 60” cutter bar widths
- 5 bat aluminum pick up reel
- Mini cleat pattern feeding belt
- Hydraulic reel height adjustment
- Hydraulic lift for header
- Floating bean saver snouts pivot mounted to header
- Adjustable gauge wheels to adjust cutter bar height
- Hydraulically driven reel, with speed control adjustable from driver’s seat
- Two optional snout styles handle problems created by lodged or tangled crops
- Belt feed heads provide rapid and thorough clean-out



## Auger Platform Head

- Drag chain feeder housing provides aggressive and even feeding for increased capacity
- Custom cutting widths available from 60” to 96”
- 5 bat aluminum pick up reel with fore/aft adjustment and adjustable height
- Adjustable skid plates
- Center auger for feeding assist

